



Sovereign Anti-Mould Grout



A flexible, hard, durable, joint filling compound suitable for walls and floors in joints up to 15 mm wide that is shrink, mould and water resistant finish.

Product Codes

Colour	3kg	10kg
White	30806182	30806183
Ivory	30806184	-
Charcoal	30806185	-
Sandstone	30806186	-
Limestone	30806187	-
Grey	30806188	30806190
Black	30806308	-

Description

Sovereign Anti-Mould Grout is a flexible joint filling compound suitable for walls and floors in joints up to 15mm wide. It dries to a hard, durable, shrink resistant, mould resistant and water resistant finish, suitable for interior and exterior use.

Form Supplied: Dry Powder

Pack Size: 3 kg, 10 kg

Colour Range: White, Ivory, Charcoal, Sandstone, Limestone, Grey and Black

Contains: Cement, aggregate powder polymer and mould inhibitor

Properties

Especially suitable for sanitary applications such as kitchens, showers, toilets and bathrooms where inhibition of fungal growth is required. Also suitable for application when tiling over under floor heating and timber panels.

Preparation

Check that the tile bed is firmly bonded and that the adhesive has dried. Rake excess adhesive out of the joint lines to allow an even depth of grout to be applied in all areas. Add Anti-Mould Grout to clean, fresh water in a clean container and mix using a mechanical stirrer. Mix thoroughly to give a smooth consistent mixture. Around 1 part water to 2 parts powder is required to form the grouting slurry. Do not add more water than is necessary as this will prolong the drying and reduce the strength of the dried grout. Under no circumstances should extra water be added to grout that is beginning to set. When the grout begins to lose workability it must be discarded. If several bags of grout are to be used then they must be from the same batch and an identical water addition used. Failure to follow these guidelines can lead to colour differences.



Sovereign Anti-Mould Grout

Technical
Data Sheet **260**

USAGE

Use a rubber squeegee to work the grout thoroughly into the tile joints, removing the excess as work proceeds. Grout residues can be removed with a lightly damp cloth or sponge up to 2 hours after application. Once the grout has hardened and dried the surface of the tiles can be polished clean with a dry cloth. All materials used such as the application tools and cleaning cloths must be clean and free of contamination likely to cause staining of the grout.

CLEAN UP

Once cured Sovereign Anti-Mould Grout will be much more difficult to remove from the face of tiles than ordinary grout. It is therefore essential that residues be removed as the application proceeds and before the grout begins to dry. Clean all tools and equipment with soapy water before the grout has set.

WORKING TIME

When mixed the grout will have a working time of 2 – 3 hours and reach final set after 24 hours. These times will alter depending on temperature; low temperatures extend the pot life and set time whilst elevated temperatures reduce them.

LIMITATIONS

Some natural stone, porous, unglazed tiles are prone to absorption of grout fines and therefore staining. Always apply grout to a spare tile to determine whether staining is likely and consult the manufacturer if necessary regarding the use of sealers prior to grouting.

Note: Sovereign Anti-Mould Grout contains a fungicide to inhibit black spot mould growth. This fungicide is active at the surface of the grout and any contamination such as soap scum etc will put a barrier between the active ingredient and mould spores therefore allowing mould to develop. It is therefore imperative that the grout is kept clean to realise the full benefit of its anti-mould properties.

COVERAGE

This will depend on the tile size, joint width and depth. The following can be used as a guide:

Joint Width	Tile Size (mm)	Wall Grout (kg)
3 mm	300 x 200 x 10	0.40 kg/m ²
6 mm	150 x 200 x 6	0.67 kg/m ²
6 mm	200 x 250 x 10	0.86 kg/m ²
8 mm	100 x 100 x 8	2.00 kg/m ²
8 mm	150 x 150 x 6	1.00 kg/m ²
10 mm	250 x 200 x 6	1.44 kg/m ²

HEALTH AND SAFETY

- ! Contact with wet cement, wet concrete or wet mortar may cause irritation, dermatitis or burns.
- ! There is a risk of serious damage to eyes. Wear suitable protective clothing, gloves and eye/face protection. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.
- ! After contact with skin wash immediately with plenty of clean water. Keep out of reach of children.
- ! Contains: Cement Portland
- ! Contains 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction



Health & safety information
available on request



Important Disclaimer

The information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that product, techniques and codes of practice are under constant review and changes occur without notice. Please ensure you have the latest updated information.



Sovereign
the gold standard in building products

Sovereign Support: 01229 870800 | www.sovchem.co.uk

FIND US HERE

