



Sovereign
the gold standard in building products

Technical
Data Sheet **269**

Sovereign Easy Paving Grout

The simple, clean, rapid solution for grouting wide joints in driveways, terraces, patios and paths.



Product Code

Grey: **30806964**

Natural: **30806973**

Description

Sovereign Easy Paving Grout is the simple, clean and fast way to grout wide joints in hard landscaping features such as paths, driveways and patios.

No mixing is required, simply pour on to the floor and brush into the joints. Once set the grout is permeable allowing paving to drain and can be used on natural stone, brick, block, concrete and clay pavers and flags.

Form Supplied: Semi-flowing aggregate

Pack Sizes: 20 kg

Colour Range: Grey & Natural

Contains: Coloured aggregate & resin

Properties

Sovereign Easy Paving grout can be used in joints from 5 mm wide and upwards. Supplied in vacuum sealed bags the grout is a resin bound aggregate that cures on contact with the air.

Once cured the grout can be pressure washed when required and is unaffected by road salts and freeze thaw conditions.

The colour is consistent throughout the mix so no more patchy areas as seen when using cement.

Preparation

The surface and sub-base must be dry as dampness inhibits the curing mechanism. Surface should be clean before commencing.

For existing areas, rake out the joints thoroughly and clean the surface with Sovereign Masonry Sterilising Wash and thoroughly rinse and allow to dry for 3 - 4 days. Joints must be a minimum of 5mm wide and 25 mm deep.

Deeper joints may be part filled with dry sand or aggregate to leave the top 25 mm for filling with Easy Paving Grout.



Sovereign Easy Paving Grout

Technical
Data Sheet **269**

USAGE

Pour Easy Paving Grout on the surface and use a coarse brush or squeegee work the grout into the joints at a 45° angle.

For best results compact the grout using a pointing trowel or rounded stick and refill any depressions as required. The surface must be protected from rain for a minimum of 18 hours, longer in cold conditions.

GENERAL

For best results seal all porous materials with the appropriate Sovereign sealer – Stone Sealer, Path & Drive Sealer. This is best done in two coats, once before and again after grouting; allow the first coat to dry before applying the grout and the grout must be cured before apply the second coat.

Temporary darkening of the surface may occur but this will weather away after a few weeks. However, when using the grey version it is possible that permanent staining can occur, therefore always test in an inconspicuous area before full application. Sealing the surface before grouting can help prevent staining, but again a test area is recommended.

CLEAN UP

Clean all tools and splashes in soapy water before the product dries.

LIMITATIONS

Limestone and particularly Indian Stone is liable to permanent staining, therefore testing is imperative before application. Low temperatures extend the curing time.

On some paving materials the Grey Grout may stain permanently, in which case the paving will take on a grey hue that will not completely disappear. Therefore, we recommend the Grey Grout is tested on a small inconspicuous area before full application.

COVERAGE

The coverage is very dependent on joint width and paving size.

For a 25 mm deep joint, 5 mm joint width in 600 x 600 paving a 20 kg pack will cover around 28 m², a 10 mm joint width will be half of this etc.

Storage: Between 5°C - 30°C.

Shelf Life: At least 12 months unopened.

HEALTH & SAFETY

- ! Contains Polybutadiene.
- ! May cause sensitisation by skin contact. Keep out of the reach of children.
- ! Avoid contact with skin and eyes. Wear suitable eye/face protection. After contact with skin, wash immediately with plenty of soap and water.
- ! In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- ! If swallowed, seek medical advice immediately and show the container or label.
- ! Dispose of this material and its container to hazardous or special waste collection point.



Health & safety information
available on request



Important Disclaimer

The information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that product, techniques and codes of practice are under constant review and changes occur without notice. Please ensure you have the latest updated information.



Sovereign
the gold standard in building products

Sovereign Support: 01229 870800 | www.sovchem.co.uk

FIND US HERE

