



## Sovereign Mortex, Redtex and Browntex

Liquid pigments for addition to mortar and concrete.



### Product Codes

Colour	1 Litre	5 Litres
Black	<b>30806445</b>	<b>30806446</b>
Red	<b>30806756</b>	<b>30806757</b>
Brown	<b>30806074</b>	<b>30806075</b>

### Description

Sovereign Mortex (black), Redtex (red) and Browntex (brown) are liquid pigment dispersion cement colourants for addition to mortar and concrete mixes that will give a permanent colour.

Form Supplied: Liquid concentrate

Pack Sizes: 1 and 5 Litres

Colour Range: Black, Red and Brown

Contains: Blend of pigments, surfactants and stabilisers.

### Properties

The use of Sovereign Mortex, Redtex or Browntex will give a permanent colour to cement based mixes.

The colour will not fade with time as the pigment becomes intricately bound in to the cured matrix, so ensuring that the colour cannot leach out.

The pigments used are also not affected by light, acid, alkali and solvent attack making them suitable for use in areas such as garage forecourts and filling stations.



# Sovereign Mortex, Redtex and Browntex

Technical  
Data Sheet

98

## PREPARATION/USAGE

It is advised that a trial mix is produced and allowed to cure (pigments appear darker when wet) to determine the exact shade required. The level of pigment added should remain constant as should the source and type of aggregate.

Sovereign cement colours should be added directly to the mix and not diluted prior to use. Add the colour to the dry cement/aggregate and mix well before adding water to the desired consistency. It must be remembered that the water content of the mix should be reduced by the same quantity.

## GENERAL

The addition rate can be varied to obtain varying levels of shade within a series of mixes to give a more natural effect, for instance, to an area of paving. Variation in colour shades can also be achieved by using grey or white cement, by using different coloured sands, and by the amount of water added to the mix.

## COVERAGE

Will depend upon colour required but as a guide we would recommend an addition rate of 10kg of pigment to 50 kg of cement.

**Storage:** Between 5°C - 30°C.

**Shelf Life:** A minimum of 12 months in unopened containers

## HEALTH & SAFETY

- ! Avoid skin and eye contact.
- ! Wash splashes from skin with soap and water, flush eyes with copious amounts of water and seek medical attention if irritation persists.



Health & safety information  
available on request



### Important Disclaimer

The information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that product, techniques and codes of practice are under constant review and changes occur without notice. Please ensure you have the latest updated information.



**Sovereign**  
the gold standard in building products

Sovereign Support: 01229 870800 | [www.sovchem.co.uk](http://www.sovchem.co.uk)

FIND US HERE

