



Sovereign Mould Eradication Additive

Mould eradication additive is used to prevent the return of black mould when added to emulsion paints or wallpaper pastes



Product Code
30806430

Description

Mould eradication additive is used to prevent the return of black mould when added to emulsion paints or wallpaper pastes and provide effective protection against mould growth.

Form Supplied: Thick cream

Pack Contents: 2 x 50 ml pots (treats 5 litres)

Colour Range: Cream

Contains: Zinc pyrithione,
3-Iodo-2-propynyl butylcarbamate,
2-octyl-2H-isothiazol-3-one.

Properties

Mould Eradication Additive is used to give standard emulsion paints, starch based wallpaper adhesives or cement based tile grout extra resistance against the growth of black mould often associated with condensation problems.

Preparation/Usage

1. Prepare surfaces by removing non-washable and loose material e.g. distemper, grease, dirt, mould or wallpaper. Dentolite Sterilising Solution can be used to soak wallpaper before removal to minimise any further mould infection.
2. Make good any surface defects and rub down to smooth finish.
3. Wash down with Dentolite Sterilising Solution using scrubbing brush or cloth. Allow to dry thoroughly. Apply second wash in badly affected areas and allow to dry before redecorating or re-painting.
4. Stir the Mould Eradication Additive into the chosen product thoroughly using a mechanical mixer. Use as normal.



Sovereign Mould Eradication Additive

Technical
Data Sheet **177**

GENERAL

There are basic measures to assist in the control of condensation and black mould. Sovereign products complements these basic controls and will prevent these problems occurring for many years.

These methods are particularly helpful in the domestic environment but can be applied equally to commercial, catering, leisure or medical establishments.

It is always important to reduce the risk of condensation by observing the following simple recommendations.

- ✓ Ensure rooms are always warm and properly ventilated, maintaining some low heating throughout the day if possible.
- ✓ When cooking, washing, bathing or drying clothes, keep the door closed and the window open - this prevents warm moist air moving to colder areas of the building.
- ✓ In cold weather keep some heating on all the time.
- ✓ If a paraffin or flueless gas heater is used ensure a window is open a little (every litre of paraffin produces about 1 litre of water).
- ✓ Improve internal/external wall insulation

Use dehumidifiers or ventilation systems where appropriate, such as Sovereign Auto ConCure 20/20.

GENERAL MAINTENANCE

Sovereign Mould Eradication Additive alone will not prevent the re-growth of mould in the long term. It is designed to be used alongside additional methods for elimination of condensation.

For long-term eradication of mould a Sovereign Auto ConCure 20/20 can be fitted in the loft space. This device acts to produce a positive air pressure within the domestic environment and will keep the relative humidity below a level that will support condensation. Unlike other similar systems the Sovereign Auto ConCure 20/20 will not cause cold draughts in winter.

LIMITATIONS

When using Mould Eradication Additive in emulsion paint, this should be the final paint layer for the Mould Eradication Additive to remain effective.

COVERAGE

2 x 50 ml are sufficient to 5 Lts of emulsion paint.

Shelf Life: 12 months unopened.

HEALTH & SAFETY

- ! Harmful if inhaled
- ! Harmful if swallowed
- ! Causes serious eye damage
- ! May cause an allergic skin reaction
- ! Keep out of reach of children
- ! Do not breathe dust/fume/mist/vapours/spray
- ! Wash face, hands and any exposed skin thoroughly after handling.
- ! Wear protective gloves/protective clothing/eye protection/face protection.



Health & safety information
available on request



Important Disclaimer

The information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that product, techniques and codes of practice are under constant review and changes occur without notice. Please ensure you have the latest updated information.



Sovereign
the gold standard in building products

Sovereign Support: 01229 870800 | www.sovchem.co.uk

FIND US HERE

