



# Sovereign

the gold standard in building products

Technical  
Data Sheet **60**

## Sovereign Multi-Purpose Panel Adhesive



Sovereign Multi Purpose Panel Adhesive is a one part gunnable synthetic, rubber based neoprene adhesive, ideal for Panel and Batten Bonding.

**Product Code**  
**30806255**

### Description

Sovereign Multi Purpose Panel Adhesive is a one part gunnable synthetic, rubber based neoprene adhesive, ideal for Panel and Batten Bonding. Sovereign Multi Purpose Panel Adhesive is highly viscous and will fill small gaps. It is easy to apply and cures rapidly.

Form Supplied: Thick Paste

Pack Sizes: 380 ml Tube x 12

Colour Range: Pale Cream

Contains: Neoprene rubber in mixed solvent.

### Properties

Use Panel Adhesive for fixing skirting boards, architraves, decorative moldings, wall panels, plasterboard, covings, picture/dado rails, carpet grippers, work tops, roof tiles, laminates to wood, concrete, brick, renders, ceramics, glass and metal. Sovereign Multi Purpose Panel Adhesive will also act as gap filler.



# Sovereign Multi-Purpose Panel Adhesive

Technical  
Data Sheet **60**

## PREPARATION/USAGE

Surfaces to be bonded should be dry, clean and free from oil, grease, dust and loose material. Cut the tip off the cartridge above the screw thread. Cut the nozzle to size according to the bead size required. Fix tube onto Sovereign Cartridge Gun.

Apply Panel Adhesive at maximum 300 mm centres on surfaces to be bonded. For light panels where the gap is small, press firmly onto the adhesive immediately and leave to cure. For heavier panels, or rough or uneven surfaces, where gap filling is required, press firmly into place, then break the bond and pull the surfaces apart.

Allow the adhesive to dry for 3 - 5 minutes, depending upon the thickness of the adhesive and the ambient conditions.

Remake the bond and press well, preferably twist or slide the item being fixed to ensure maximum adhesion.

## GENERAL

Heavy items should be supported until the adhesive is completely cured (approximately 24 hours) - carrying out a local trial is recommended. At least one surface must be porous.

## CLEAN UP

Sovereign Contact Cleaner

## LIMITATION

Not suitable for use with polystyrene or on asphalt floors.

## COVERAGE

15 running metres per cartridge - 5 mm<sup>2</sup> bead

**Storage:** Between 5°C - 30°C.

**Shelf Life:** 12 months unopened.

## HEALTH & SAFETY

- ! Keep out of reach of children.
- ! Keep away from sources of ignition including pilot lights. No smoking.
- ! Causes skin irritation.
- ! Keep container tightly closed in a cool, well-ventilated place.
- ! Take precautionary measures against static discharges. Use only in well ventilated areas.



Health & safety information  
available on request



### Important Disclaimer

The information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that product, techniques and codes of practice are under constant review and changes occur without notice. Please ensure you have the latest updated information.



**Sovereign**  
the gold standard in building products

Sovereign Support: 01229 870800 | [www.sovchem.co.uk](http://www.sovchem.co.uk)

FIND US HERE

