



Sovereign

the gold standard in building products

Technical
Data Sheet **274**

Sovereign Plasprime X[®]



Sovereign PLASPRIME X[®] is a next generation of primer for the plastering and rendering professional. Using patented Plasprime[®] technology, Plasprime X[®] it has all the same properties of the original but is now suitable for external use. Plasprime X[®] is grey in colour but is still a green product as it contains around 20% of recycled material.

Product Code
30806268

Description

PLASPRIME X[®] can be used on virtually any surface to provide the perfect preparation to which plaster and render is to be applied.

Form Supplied: Viscous Liquid

Pack Sizes: 10 Litres

Colour Range: Grey

Contains: Blend of polymer, additives and 20% recycled material.

Properties

Plasprime X[®] is particularly useful when dashing on to new block-work where it can replace the coat of water resistant render applied before the receiver coat.

Plasprime X[®] can also be used internally for re-skimming old walls and is particularly useful when ceramic tiles are required to be plastered



PREPARATION/USAGE

The surface should be clean and sound; treat any loose or flaking material mechanically to remove. Existing paint should be checked for soundness and adhesion. Do not apply directly on to wallpaper. If using to bond cement render to the background then it is assumed that the surface is sufficiently strong to support the weight of the render.

GENERAL

Apply PLASPRIME X[®] with a soft brush to give an even texture over the entire surface and allow to thoroughly dry. The drying time is dependant on the surface porosity and environmental conditions.

Once the primer has dried apply plaster or render in the normal manner. PLASPRIME X[®] can be used over most building materials such as brick, block, concrete, plaster, render, well adhered paint and adhesive residues, artex and plasterboard.

CLEAN UP

Clean all tools and splashes in water before the product dries

LIMITATIONS

PLASPRIME X[®] will not make up for defective surfaces and the bond will only be as good as the weakest part of the system i.e. when applied on to paint. Sovereign are not responsible for the failure of an underlying substrate.

COVERAGE

The coverage of PLASPRIME[®] is dependent on the surface smoothness and absorbency. As a guide, 1 litre of PLASPRIME[®] will cover approximately 2 - 4 square metres.

Storage: Between 5°C - 30°C.

Shelf Life: A minimum of 12 months in unopened containers.

HEALTH & SAFETY

- ! Avoid skin and eye contact.
- ! Wash splashes from skin with soap and water, flush eyes with copious amounts of water and seek medical attention if irritation persists.
- ! EUH208 - Contains 2-methyl-2H-isothiazol-3-one [MIT] & reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]. May produce an allergic reaction.



Health & safety information
available on request



Important Disclaimer

The information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that product, techniques and codes of practice are under constant review and changes occur without notice. Please ensure you have the latest updated information.



Sovereign
the gold standard in building products

Sovereign Support: 01229 870800 | www.sovchem.co.uk

FIND US HERE

