



Sovereign Renderlite Finishing Plaster

Sovereign Renderlite Finishing Plaster is a high impact plaster for use as the final coat on to Sovereign Renderlite Renovating Plaster or a sand/cement render.



Product Code
30806773

Description

Renderlite Finishing Plaster cures to form a hard wall finish plaster that allows the walls to breathe.

Form Supplied: Powder

Pack Sizes: 25 kg bag.

Colour Range: Grey, off white

Contains: Lime gypsum, fine aggregate.

Properties

Sovereign Renderlite Finish Plaster has excellent adhesion and impact resistance and resists the passage of salts. Once mixed it can be re-tempered and used for up to 60 minutes therefore, minimising waste.

Preparation

Apply on to a suitable prepared background plaster such as Sovereign Renderlite, Ready Render or ordinary sand: cement plaster. It is not however suitable for use on plasterboard.



Sovereign Renderlite Finishing Plaster

Technical
Data Sheet **87**

MIXING

Add Sovereign Renderlite finish to water and bring to a workable consistency. Allow the mix to rest for 5 minutes and remix adding a small quantity of water if necessary. During use Renderlite Finishing Plaster may give the appearance of going off. However this is not the case and the mix can be reworked with the trowel. Renderlite Finishing Plaster will continue to thicken and can be reworked for up to 60 minutes which should allow plenty of time for the material to be used up without waste.

USAGE

Apply at 1.5 to 3 mm thickness to give a smooth surface. Renderlite Finishing Plaster cannot be over polished to give a glazed surface. This is because polished plaster causes problems when painting or tiling onto normal gypsum finishes.

Due to its nature the application of Renderlite Finishing Plaster feels different from normal gypsum plaster and this must be considered during use.

Once set the plaster will be very hard and creamy white in colour.

GENERAL

When the Renderlite system is used after the insertion of a DPC then it should be left as long as possible before the application of a paint coating, wallpapering must be delayed for 6 months.

If tiles are to be applied then these should be fixed directly to the backing coat using one of Sovereigns powdered tile adhesives.

LIMITATIONS

Renderlite Finish is not suitable for use on plasterboard.

COVERAGE

12.5 m² per 25 kg bag @ 1 mm thickness

Storage: This product must be stored in a dry place, free from moisture contact. Do not store in direct contact with the ground.

Shelf Life: 6 months in unopened bags.

HEALTH & SAFETY

- ! Contains: Calcium hydroxide
- ! Causes skin irritation
- ! Causes serious eye damage
- ! May cause respiratory irritation
- ! If medical advice is needed, have product container or label at hand
- ! Keep out of reach of children
- ! Do not breathe dusts or mists
- ! Wear protective gloves/protective clothing and eye/face protection



Health & safety information
available on request



Important Disclaimer

The information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that product, techniques and codes of practice are under constant review and changes occur without notice. Please ensure you have the latest updated information.



Sovereign
the gold standard in building products

Sovereign Support: 01229 870800 | www.sovchem.co.uk

FIND US HERE

