



Sovereign Wall Tile Grout

Sovereign Wall Tile Grout is a cement-based polymer modified joint filling compound for tile joints up to 3 mm wide



Product Codes

Colour	1.5 kg	3 kg	12.5 kg
White	30806583	30806584	30806664

Description

Sovereign Wall Tile Grout is a cement-based polymer modified joint filling compound for tile joints up to 3 mm wide around all types of ceramic floor and wall tiles. Wall Tile Grout is formulated to provide a non-slump, readily compactable grouting slurry, which can be easily applied across all types of ceramic tiled surfaces using a sponge or rubber squeegee.

Form Supplied: Powder

Pack Sizes: 1.5 kg, 3 kg, 12.5 kg

Colour Range: White, Ivory

Contains: White Cement, aggregate and specialist additives

Properties

Sovereign Wall Tile Grout will dry to a hard, durable and water-resistant finish, suitable for internal and external locations. In fully immersed locations, the inclusion of Sovereign SBR Bonding Agent in the grout mix can enhance water repellent properties.

Preparation

Check that all tiles are securely fixed and that the adhesive has thoroughly dried before applying any load or pressure to the tiled surface.

Ensure all joints are raked clear of any excess adhesive residues to allow an even and consistent depth of grout to be applied in all areas.

Tiling applied to wood panelled surfaces, where slight movement is likely should be grouted with White Tile Grout mixed with Sovereign SBR Bonding Agent diluted 1:3 with water to improve flexural and adhesive strength.

Note: Certain types of tile may be porous and hence prone to surface discolouration. Natural stone and porous, un-glazed tiles are particularly prone to absorption of grout fines.



MIXING

Sovereign Wall Tile Grout should be added to water in a clean container whilst mechanically stirring and mixing thoroughly to give a smooth, consistent and easily worked mortar.

The recommended mixing proportions by volume are approximately 1 part water to 2 parts powder (4.2 litres per 10 kg of powder). Do not add more water than is necessary as this may prolong drying and significantly reduce the compressive strength of the cured grout.

Part-used grout should never be "freshened up" with later water additions, but should always be discarded once it appears to lose workability.

In ideal conditions (20°C), Wall Tile Grout will remain workable for 2 to 3 hours and then reach final set after about 24 hours.

When grouting over a large area using several bags of grout, ensure all mixes are from the same batch and that a consistent and identical water addition is used for each mix.

USAGE

Apply mixed grout to a spare tile to determine whether staining is likely and consult the tile manufacturer prior as to whether they recommend a suitable sealing compound to protect the surface. Use a rubber squeegee, or smooth sponge to work the grout thoroughly and consistently into the tile joints, removing the excess as work proceeds across tiled area.

Fine grout residues can be washed away with a lightly damp cloth or sponge up to 2 hours after application, with a final clean finish being achieved using a dry cloth to polish the surface when the joints have dried and hardened.

Sovereign Wall Tile Grout mixed with SBR Bonding Agent will be more difficult to remove from tiled surfaces when dry therefore extra care is necessary to ensure residues are completely removed as the application proceeds.

LIMITATIONS

Tile adhesives and grouts must not be regarded as a primary waterproofing system.

When tiling on to moisture sensitive backgrounds, such as plaster, plasterboard and timber etc then measures should be employed to prevent moisture damage and leakage.

An ideal solution is the use of Sovereign Watertite for wet rooms, shower enclosures and bathrooms. For swimming pools and external masonry then the use of Sovereign Hey'di K11 Tanking System should be considered.

COVERAGE

This will depend on the tile size, joint width and depth. The following can be used as a guide.

Joint Width	Tile Size (mm)	Wall Grout (kg)
2 mm	150 x 200 x 6	0.21 kg/m ²
2 mm	200 x 250 x 10	0.27 kg/m ²
2 mm	150 x 150 x 4	0.17 kg/m ²
3 mm	300 x 200 x 10	0.40 kg/m ²
3 mm	100 x 100 x 4	0.33 kg/m ²
3 mm	150 x 150 x 4	0.25 kg/m ²

Storage: Between 5°C - 30°C.

Shelf Life: 12 months unopened.

HEALTH AND SAFETY

- ! Avoid skin and eye contact.
- ! Wash splashes from skin with soap and water, flush eyes with copious amounts of water and seek medical attention if irritation persists.



Health & safety information
available on request



Important Disclaimer

The information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that product, techniques and codes of practice are under constant review and changes occur without notice. Please ensure you have the latest updated information.



Sovereign

the gold standard in building products

Sovereign Support: 01229 870800 | www.sovchem.co.uk

FIND US HERE

